



EXCEPTIONAL RISKS RELATING TO THE WORKS ASSOCIATED WITH THIS DRAWING ARE IDENTIFIED BELOW. CONSTRUCTION RISK: XXX NOTES 1.2m Max Taper Cone Spacings 9m Max Longitudinal Cone Spacings 1.0m Min Footway / Walkway To Be Maintained 0.5m Min Sideways Safety Zone 0.5m Min Longways Safety Zone 3.0-3.5m Running Lane Measurements Will Be Subject To Survey Minimum P.P.E requirements to be worn during installation Hard Hats, Glasses, Gloves, Boots, High Visibilty Clothing Hard Hats, Glasses, cloves, boots, Inply visionity Coming Minimum requirements for ALL sign placement please follow instructions below without exception

Minimum height 2.2m over footpath

Minimum height 2.5m over cyclepath

Minimum sideways clearence carriageway!Footpath 450mm

Frames keep 1 mclearence on footpath

All frames must be sandbagged Any issues not allowing you to follow regulations please contact the office or out of hours. FIRST ISSUE By Date Suffix REVISION DETAILS **DRAFT Chevron** Traffic Management CG0001 Aston Road Witnew **OX29 7QW**  
 signed
 Drawn
 Checked
 Approved
 Date

 T.B
 T.B
 B.C
 B.C
 01/11/2023
 Scale @ A3 NOT TO SCALE

Drawing Number
Project Code/PIN 1 Originator I Volume
HE000000 CHEV TTM

PO\_XX\_XX\_X DR X 0001

Xxx

THIS DRAWING IS TO BE USED ONLY FOR THE PURPOSE OF ISSUE THAT IT WAS ISSUED FOR AND IS SUBJECT TO AMENDMENT.

© Crown copyright and database rights 2021 OS 000000000